

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A transport securing arrangement for a side extension arm of a vehicle, said transport securing arrangement comprising:

~~having~~ a locking device; and

~~a~~ ~~an additional~~ securing hook,

wherein said locking device and said securing hook are arranged such that both said locking device and said securing hook are operable to act on the side extension arm, and characterised in that the

wherein said locking device is arranged in relation to said the securing hook in such a way that a release of the said locking device leads to a release of said the securing hook from an its anchorage position.

2. (Currently Amended) A transport securing arrangement as set forth in claim 1, wherein characterised in that the said securing hook is pivotably supported pivotably.

3. (Currently Amended) A transport securing arrangement as set forth in claim 1, further comprising a spring, wherein said characterised in that there is provided a spring which urges the said securing hook into the anchorage position.

4. (Currently Amended) A transport securing arrangement as set forth in claim 1, wherein characterised in that the said locking device is rotatably supported rotatably.

5. (Currently Amended) A transport securing arrangement as set forth in claim 4, wherein
~~characterised in that the~~ said locking device is releasable by rotation of said locking device.

6. (Currently Amended) A transport securing arrangement as set forth in claim 5, wherein
~~characterised in that the~~ said locking device is releasable upon by rotation of said
locking device, and
wherein the release of said locking device is independent ~~independently of the~~ a direction
of rotation of said locking device.

7. (Currently Amended) A transport securing arrangement as set forth in claim 4, further
comprising a pin,
wherein ~~characterised in that the~~ said locking device has at least one guide surface
extending in an inclined manner ~~inclinedly~~ relative to a ~~the~~ longitudinal center line of ~~the~~ said
locking device, and
wherein upon rotation of ~~the~~ said locking device, ~~the~~ said at least one guide surface of
said locking device slides along said ~~[[a]]~~ pin.

8. (Currently Amended) A transport securing arrangement as set forth in claim 1, further
comprising a spring, wherein ~~characterised in that the~~ said locking device is urged in a ~~the~~
direction of a ~~the~~ locking position by said ~~[[a]]~~ spring.

9. (Currently Amended) A transport securing arrangement as set forth in claim 1,
wherein characterised in that the said locking device includes an eccentrically shaped
portion, and
wherein said securing hook partially bears against ~~an~~ said eccentrically shaped portion of
the said locking device.